



# Wallflower Smart Monitor™

## Installation Guide

For 3-Wire & 4-Wire Stoves



Wallflower Smart Monitor™ is compatible with  
Apple iPhone® and Google Android™



Smart Monitor (3-wire) and Smart Monitor (4-wire) shown above



Conforms to UL Std. 498A,  
Cert. to CSA Std. C22.2 No. 42  
For disconnecting use only



This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.  
CAN ICES-3 (B)/NMB-3(B)  
Contains Transmitter CC32xx Module  
FCC ID: Z84-CC3200MGR1  
IC ID: 4511-CC3200MGR1

© 2017 Wallflower Labs Inc. or its affiliates. All rights reserved. Wallflower, the Wallflower logo, and the Wallflower Smart Monitor are trademarks of Wallflower Labs Inc. or its affiliates, registered in the U.S. and other countries. Apple, the Apple logo, and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. Google, Google Play and Android are trademarks of Google Inc., registered in the U.S. and other countries. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Patent pending.



Smart Monitor (4-wire) installation shown

## Installation Steps

1. Turn off circuit breaker for stove circuit
2. To access stove power cord, pull stove away from wall or remove stove drawer
3. Unplug stove power cord
4. Plug Smart Monitor into outlet then plug power cord into Smart Monitor
5. Push stove back and ensure anti-tip bracket engages or replace stove drawer
6. Turn on circuit breaker for stove circuit
7. Download Wallflower App from App Store or Google Play and follow setup



### WARNING

Turn Off Circuit Breaker Before Install

## Resetting To Factory Default

After setting up your Wallflower Smart Monitor using the App, if resetting to factory default settings is ever required, simply cycle your circuit breaker OFF and ON per the following:

1. Turn OFF circuit breaker
2. Turn ON circuit breaker, wait 5 seconds
3. Turn OFF circuit breaker
4. Turn ON circuit breaker, wait 5 seconds
5. Turn OFF circuit breaker
6. Turn ON circuit breaker

Your Smart Monitor will beep to let you know that it has been reset and is ready for setup. If you have trouble factory resetting your Smart Monitor, visit [wallflower.com/support](https://wallflower.com/support)

## Technical Specifications

### Model No. WFA001

125/250V~ 4-wire, 50A, 14-50R

### Model No. WFA002

125/250V~ 3-wire, 50A, 10-50R

## Questions?

If you have questions or difficulties, please visit [wallflower.com/install](https://wallflower.com/install) or email [support@wallflower.com](mailto:support@wallflower.com)